

1. (Currently amended) A face wall for a motor vehicle, the face wall having a first wall and a second wall at a spacing from the first wall wherein the first wall has a recess having a reinforced edge region to accommodate a brake booster which is fastened solely to the first wall.

2. (Cancelled)

3. (Currently amended) A face wall according to claim 2 1, wherein the brake booster has an edge surface which rests on the edge region of the recess.

4. (Previously presented) A face wall according to claim 3, wherein an elastomer ring is arranged on the edge surface of the brake booster on the side oriented towards the edge region.

5. (Previously presented) A face wall according to claim 1 wherein the brake booster is screwed to the first wall.

6. (Currently amended) ~~A face wall according to claim 1 wherein~~ A face wall for a motor vehicle, the face wall having a first wall and a second wall at a spacing from the first wall wherein the first wall has a recess to accommodate a brake booster which is fastened solely to the first wall, the second wall ~~has~~ having a feed-through aperture for the brake booster.

7. (Previously presented) A face wall according to claim 6, wherein the gap between the feed-through aperture and brake booster is between 1 mm and 20 mm in the region of the feed-through aperture.

8. (Previously presented) A face wall according to claim 6 wherein the face wall has curvatures in the region of at least one of the recess and the feed-through aperture.

9. (Currently amended) ~~A face wall according to claim 1 wherein~~ A face wall for a motor vehicle, the face wall having a first wall and a second wall at a spacing from the first wall wherein the first wall has a recess to accommodate a brake booster which is fastened solely to the first wall, the face wall ~~has~~ having reinforcing webs in the region of the recess.

10. (Currently amended) ~~A face wall according to claim 1 wherein~~ A face wall for a motor vehicle, the face wall having a first wall and a second wall at a spacing from the first wall wherein the first wall has a recess to accommodate a brake booster which is fastened solely to the first wall, foam is being arranged between the first wall and the second wall.

11. (Currently amended) ~~A face wall according to claim 1 wherein~~ A face wall for a motor vehicle, the face wall having a first wall and a second wall at a spacing from the first wall wherein the first wall has a recess to accommodate a brake booster which is fastened solely to the first wall, the brake booster is being covered on its outer surface with a foam-repelling material.

12. (Previously presented) A face wall according to claim 1 wherein the face wall is a module for mounting in a face wall frame of the body of a motor vehicle.

13. (Previously presented) A face wall according to claim 1 wherein at least one of the first wall and the second wall is formed from one of plastics material and metal.

14. (Previously presented) A motor vehicle containing a face wall according to claim 1.

15. (New) A face wall according to claim 1 wherein the face wall has reinforcing webs in the region of the recess.

16. (New) A face wall according to claim 1 wherein foam is arranged between the first wall and the second wall.

17. (New) A face wall according to claim 1 wherein the brake booster is covered on its outer surface with a foam-repelling material.

18. (New) A motor vehicle containing a face wall according to claim 6.

19. (New) A motor vehicle containing a face wall according to claim 9.

20. (New) A motor vehicle containing a face wall according to claim 10.

21. (New) A motor vehicle containing a face wall according to claim 11.